

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 61428

## Type of light source:

|   |           |                                 |     |
|---|-----------|---------------------------------|-----|
| Lighting technology used:                           | LED       | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | VDE WIRES |                                 |     |
| Mains or non-mains:                                 | MLS       | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No        | Envelope:                       | -   |
| High luminance light source:                        | No        |                                 |     |
| Anti-glare shield:                                  | No        | Dimmable:                       | No  |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|  |                            |  |   |
|--|----------------------------|--|---|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 150                        | Energy efficiency class  | D   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 18 750 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000   |
| On-mode power ( $P_{on}$ ), expressed in W   | 150,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 82  |
| Outer dimensions without separate control gear, light-   | Height                     | 320  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                      | 23   |   |
|  | Depth                      | 32   |   |
|  |                            |  | See image in last page  |

|   |                   |  |                |
|---|-------------------|--|----------------|
| ing control parts and non-lighting control parts, if any (millimetre)   |                   |  |                |
| Claim of equivalent power <sup>(a)</sup>  | Yes               | If yes, equivalent power (W)                                       | 1 000          |
|   |                   | Chromaticity coordinates (x and y)                                 | 0,313<br>0,337 |
| <b>Parameters for directional light sources:</b>  |                   |  |                |
| Peak luminous intensity (cd)  | 725               | Beam angle in degrees, or the range of beam angles that can be set | 120            |
| <b>Parameters for LED and OLED light sources:</b>   |                   |  |                |
| R9 colour rendering index value   | 2                 | Survival factor  | 0,95           |
| the lumen maintenance factor  | 0,92              |  |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |                   |  |                |
| displacement factor (cos $\phi_1$ )   | 0,97              | Colour consistency in McAdam ellipses                              | 4              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | .. <sup>(b)</sup> | If yes then replacement claim (W)                                  | -              |
| Flicker metric (Pst LM)   | 0,0               | Stroboscopic effect metric (SVM)                                   | 0,0            |

(a).': not applicable;

(b).': not applicable;