

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 61502

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	VDE WIRES		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------


### General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	200	Energy efficiency class	C
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	30 000 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode power ( $P_{on}$ ), expressed in W	200,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, light-	Height	160	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	300	
	Depth	300	
			See image in last page


ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	1 800
		Chromaticity coordinates (x and y)	0,346 0,359
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	3 000	Beam angle in degrees, or the range of beam angles that can be set	90
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	3	Survival factor	0,96
the lumen maintenance factor	0,94		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,99	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	.. <sup>(b)</sup>	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a).': not applicable;

(b).': not applicable;



SDCM: 3.2



x=0.3460 y=0.3590 F5000

Model placed on the Union market from 01/07/2024.



**EPREL registration number:** 890676

<https://eprel.ec.europa.eu/qr/890676>

**Supplier:** GLOBOSTAR GROUP SINGLE MEMBER P.C. (Importer)

**Website:** [www.globostar.gr](http://www.globostar.gr)

**Customer care service:**

**Name:** GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP

**Website:** [www.globostar.gr](http://www.globostar.gr)

**Email:** [eprel2021@globostar.eu](mailto:eprel2021@globostar.eu)

**Phone:** 00306980878477

**Address:**

1st Km Old National Road Katerinis-Thessalonikis 1  
60100 KATERINI  
Greece