

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR® GROUP, THESSALONIKIS 98, 60132 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 61024

## Type of light source:

|   |                                  |                                 |      |
|---|----------------------------------|---------------------------------|------|
| Lighting technology used:                           | LED                              | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | T5 LINKABLE WIRES TERMINAL BLOCK |                                 |      |
| Mains or non-mains:                                 | MLS                              | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                               | Envelope:                       | -    |
| High luminance light source:                        | No                               |                                 |      |
| Anti-glare shield:                                  | No                               | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                     | Parameter  | Value                              |
|--|---------------------------|--|------------------------------------|
| <b>General product parameters:</b>   |                           |  |                                    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 18                        | Energy efficiency class  | E                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 2 200 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 500                              |
| On-mode power ( $P_{on}$ ), expressed in W   | 17,7                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 84                                 |
| Outer dimensions without separate con-   | Height                    | 1 200  | Spectral power distribution in the |
|  | Width                     | 23   |                                    |
|  | Depth                     | 40   |                                    |
|  |                           |  | See image in last page             |

|   |                   |  |                                       |                |
|---|-------------------|--|---------------------------------------|----------------|
| trol gear, lighting control parts and non-lighting control parts, if any (millimetre)                                   |                   |  | range 250 nm to 800 nm, at full-load  |                |
| Claim of equivalent power <sup>(a)</sup>  | Yes               |  | If yes, equivalent power (W)          | 140            |
|   |                   |  | Chromaticity coordinates (x and y)    | 0,367<br>0,372 |
| <b>Parameters for LED and OLED light sources:</b>   |                   |  |                                       |                |
| R9 colour rendering index value   | 6                 |  | Survival factor                       | 1,00           |
| the lumen maintenance factor  | 0,94              |  |                                       |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |                   |  |                                       |                |
| displacement factor (cos $\phi_1$ )   | 0,92              |  | Colour consistency in McAdam ellipses | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | .. <sup>(b)</sup> |  | If yes then replacement claim (W)     | -              |
| Flicker metric (Pst LM)   | 0,0               |  | Stroboscopic effect metric (SVM)      | 0,0            |

(a) : not applicable;

(b) : not applicable;

