Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National

Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model	identifier:	SKU: 73705
IVIOUCI	idelitiiei.	3110.73703

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	WIRES		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		60 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	10 000		
On-mode power (P _{on}), expressed in W		0,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	70		
Outer dimen-	Height	10	Spectral power dis-	See image		
sions without	Width	35	tribution in the	in last page		
separate con- trol gear, light-	Deptil 255		range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	10			
		Chromaticity coordi-	0,144			
		nates (x and y)	0,045			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-100	Survival factor	0,90			
the lumen maintenance factor	0,90					

(a)'-': not applicable; (b)'-': not applicable;

