Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National

Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Mode	l identifier:	SKU: 70602
------	---------------	------------

Type	of I	ight	sοι	ırce:
------	------	------	-----	-------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	WIRES		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	mption in on- 00 h), rounded st integer	4	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in , in a wide cone arrow cone (90º)	156 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	3,9	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	70
Outer dimen-	Height	12	Spectral power dis-	See image
sions without	Width	12	tribution in the	in last page
separate con- trol gear, light-	Depth	1 000	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15
		Chromaticity coordi-	0,440
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value 1		Survival factor	0,90
the lumen maintenance factor	0,90		

(a)'-': not applicable; (b)'-': not applicable;



