

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR® GROUP, THESSALONIKIS 98, 60132 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 60459

## Type of light source:

|   |                      |                                 |      |
|---|----------------------|---------------------------------|------|
| Lighting technology used:                           | LED                  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Wires-Terminal Block |                                 |      |
| Mains or non-mains:                                 | MLS                  | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                   | Envelope:                       | -    |
| High luminance light source:                        | No                   |                                 |      |
| Anti-glare shield:                                  | No                   | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                     | Parameter  | Value                  |
|--|---------------------------|--|------------------------|
| <b>General product parameters:</b>   |                           |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 12                        | Energy efficiency class  | E                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 400 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 500                  |
| On-mode power ( $P_{on}$ ), expressed in W   | 12,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 82                     |
| Outer dimensions without   | Height                    | Spectral power distribution in the   | See image in last page |
|  | Width                     |  |                        |
|  | Depth                     |  |                        |

|   |      |                                       |                                      |  |
|---|------|---------------------------------------|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |      |                                       | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>  | Yes  | If yes, equivalent power (W)          | 75                                   |  |
|   |      | Chromaticity coordinates (x and y)    | 0,363<br>0,361                       |  |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                       |                                      |  |
| R9 colour rendering index value   | 3    | Survival factor                       | 1,00                                 |  |
| the lumen maintenance factor  | 0,92 |                                       |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |                                       |                                      |  |
| displacement factor (cos $\phi_1$ )   | 0,80 | Colour consistency in McAdam ellipses | 4                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)     | -                                    |  |
| Flicker metric (Pst LM)   | 0,0  | Stroboscopic effect metric (SVM)      | 0,0                                  |  |

(a) : not applicable;

(b) : not applicable;

