Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National

Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model identifier: SKU: 60365

Type	of	light	sour	ce:
------	----	-------	------	-----

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	VDE WIRES				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Duradicat negregations					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	260 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pow pressed in W	ver (P _{on}), ex-	2,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84		
Outer dimen-	Height	60	Spectral power dis-	See image		
sions without	Width	100	tribution in the	in last page		
separate control gear, light-	Depth	100	range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	25		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	12	Survival factor	0,94		
the lumen maintenance factor	0,92				

(a)'-': not applicable; (b)'-': not applicable;



