



LTseries **LT215** **LT215T**

Two-way Loudspeaker System

The **LT215** is a compact, 15" LF driver and 1.4" exit HF driver, 2-way, highly weather-resistant full range loudspeaker with high SPL, the body is made of engineering plastic injection molding. The system conforms to IP56 international standard. LT215T is equipped with multi-tap transformer based on LT215.

LT215是一款15寸两分音全天候音箱，箱体设计优先考虑全天候使用环境和高声压输出，采用一只15"中低音单元，一只1.4"喉口75芯钛膜高音驱动器，中低音与高音全部采用号角负载设计，箱体采用工程塑胶注塑而成。LT215T是在LT215的基础上配置多种输出功率选择功能的定压音箱。产品满足IP56国际标准。

FEATURES

- Highly weather-resistant IP56 rating
- Engineering plastic injection molding
- High SPL
- Horn loaded design for HF driver and LF driver
- Good used for sports facilities, stadiums, water parks, and a wide variety of other outdoor venue types.



产品特征

- 高质量单元配置，工程塑胶箱体
- 号角负载设计，高音压级输出
- 单元隐藏式安装，适应全天候使用
- 超长品质保证期：品质与信心的保证

适用范围

- 用于中远程语言扩声
- 广场、主题公园、景区扩声

CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

INPUT VOLTAGE

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

LT215

50Hz-18kHz

45Hz-20kHz

1×15"(385mm)/3"voice coil LF

1×1.4"(36mm)/3"voice coil HF

400W RMS,1600W peak

103dB 1watt/1 metre

129dB continuous,135dB peak

8 ohms nominal

70°×40°

1.5kHz passive

covered barrier strip terminals

610mm×545mm×595mm

28.5 kg/pc

31.5 kg/pc

LT215T

50Hz-18kHz

45Hz-20kHz

1×15"(385mm)/3"voice coil LF

1×1.4"(36mm)/3"voice coil HF

100V

75W/150W/300W/OFF/8Ω 400W

103dB 1watt/1 metre

129dB continuous,135dB peak

8 ohms nominal

70°×40°

1.5kHz passive

covered barrier strip terminals

610mm×545mm×595mm

31 kg/pc

34 kg/pc